

DM01D11

LED Work Light

IP54



- High-power LED light source, higher luminous efficiency;
- No Flickering protection can protect your eyes;
- LED light source is more energy efficient and has a longer service life;
- Robust and durable structural design, anti-impact protection;
- Waterproof structure design, protection in wet environment;
- Ergonomic handle design makes the hand feel more comfortable;
- The high strength PC outer tube is not easy to break;
- Flexible and rotatable hook for easy mobile use

Technical Data

Power Consumption with LED Driver LED燈具包括LED驅動電源功率 Consumo de energía con controlador de LED	13W
Input Voltage / 輸入電壓 Voltaje de entrada	AC220V-240V 50/60Hz
Power Factor / 功率因數/Factor de potencia	PF: >0.5
Light Source Brand-光源品牌-Fuente de luz de marca	80 pcs LED SMD -CREE U.S.A
Color Temperature and Color 色溫和顏色 Temperatura y color del color	6500K
Luminaire Efficacy 燈具效率 La eficacia de la luminaria	1300 LM (100lm/w)
Color Rendering Index-顯色指數 Índice de reproducción cromática	>80
Ingress Protection-防護等級 Protección de ingreso	IP54
Socket 插座 Enchufe	UK BS standard socket 英國BS標準插座 Toma estándar BS del Reino Unido
Housing materials 外殼材料 Materiales de la carcasa	Polycarbonate and ABS 聚碳酸酯和ABS Policarbonato y ABS
Cable Length: 電纜長度: Longitud del cable:	• 8 Meter 3 x1.0 sq.mm PC Cable • 8米3 x1.0平方毫米PC電纜 • Cable para PC de 8 metros y 3 x 1.0 mm cuadrado
Housing Color 外殼顏色 color de la carcasa	GREY 灰色 Gris
Operating Temperature Range / 工作溫度範圍 Rango de temperatura de funcionamiento	-30 °C / +50 °C
Operating Humidity	0~90%, non-condensing-
Dimension (LxWxH) / 尺寸 / Dimensión	L360x W 55x H: 40mm
Net Weight / 淨重/ Peso Neto	980g
Certification	IP54

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your need and write its corresponding code on the appropriate line to form the product code.

Example product code:

DM01D11 -